

US30 UNIVERSAL RADIAL SAW

Motor	kW	5.5 – Volt 400 / 3 / 50 Hz
Total weight	Kg	900
COMPLETE WITH:		
Widia blade	ø mm	550, F30
Blade speed	RPM	2800
Cutting speed	m/sec	80
Horizontal axis - Rotation		from +30° to +150°
Vertical axis - Tilt		from +30° to +120°
Automatic rotation and tilt managed by programmer on board the machine		
1 m roller table, 90 mm diameter rollers on the right of the blade	No.	1
1 m roller table, 90 mm diameter rollers on the left of the blade	No.	1
Vertical pneumatic clamp	No.	2
No. 3 intake vents	ø mm	120

CUTTING CAPACITY:		
Cutting capacity at 90°	mm	510
Cutting capacity at 120° in rotation	mm	435
Cutting capacity at 45° in rotation	mm	350
Cutting capacity at 30° in rotation	mm	255
Cutting height at 90°	mm	210
Cutting height at 60° tilt:	mm	165 per 90° angle in rotation
Cutting height at 45° tilt:	mm	130 per 90° angle in rotation
Cutting height at 30° tilt:	mm	80 per 90° angle in rotation



STROMAB

EXPERTS IN CROSSCUTTING SOLUTIONS SINCE 1965

STROMAB SPA

42012 CAMPAGNOLA EMILIA (RE) Italy
Via Zuccardi 28/a - Z.I. Ponte Vettigano
Tel. (0522) 1933300 - Fax (0522) 1933361
info@stromab.com - www.stromab.com